


ARRONE® Panic & Emergency Exit Hardware

ARRONE® AR880 Single Panic Bolt



Application

- Suitable for single or double doors with plain meeting stiles. Suitable for single doors up to 2440mm height x 1220mm wide (extended top shoots available).
- SUITABLE FOR USE IN OPEN PUBLIC AREAS (in accordance with BS EN1125: 1997)
- Please note: For double NON rebated plain edge doors fit 2 x AR880

Standards and Certification



Quality & Performance: Successfully type tested to all the requirements of BS EN1125: 1997 + A1:2001

3	7	6	1	1	3	2	2	A
---	---	---	---	---	---	---	---	---



Fire Safety: Included in a successful fire test to BS EN1634 Part 1: 2000. For use on 30 min fire doors



CE Marked: Declaration of conformity available on request

Standard Features

- Automatic top trip
- Two-point locking
- Diecast control boxes
- Follower on main box for use with ARRONE® locking attachments
- Anti-thrust device preventing leverage of top and bottom shoots
- Oval steel rods
- Self handing
- Supplied with “W” clip for use with a rim cylinder on external side
- “Push Bar To Open” signage supplied

Finishes

- Silver
- Gold
- Black
- Polished Brass
- Polished Stainless Steel – Polished Chrome
- Satin Stainless Steel – Satin Chrome
- RAL colours to special order only

Guarantee

- Supported by a 2 Year Guarantee

ID NO	PRODUCT REF	DESCRIPTION	FINISH
8510689	AR880-SE	Single Panic Bolt	Silver
8510640	AR880-GE	Single Panic Bolt	Gold
8510696	AR880-SSS	Single Panic Bolt	SSS
8510654	AR880-PB	Single Panic Bolt	PB
8510577	AR880-BL	Single Panic Bolt	Black
8510584	AR880-CH	Single Panic Bolt	PSS